



Agpoint Australia

Agpoint Boron Discs & Coulters.....Your Guarantee of Quality!!!
 Recommended Retail Price List No. 179 Effective 1st November 2023 (GST Not Included)



Please Note: Prices Subject To Change Without Prior Notice

Part No	Similar To McCOY	R.R.P	Gauge mm	Style	Centre Hole	Radial Holes	P.C.D. mm	Radial Code	Application	Unit KG
11" (275mm) Coulters										
C1103			3	PLAIN-DB	72MM DIA.	5 X 9MM DIA.	95		CSN 470 DRILLS	1.30
6100			4	PLAIN-DB	72MM DIA.	5 X 9MM DIA.	95	R22	CSN 470 DRILLS	1.70
6151			4	PLAIN-DB	45MM DIA.	5 X 7MM DIA.	95	R42	AITCHISON	1.70
6154 (11 1/2")	ALT. 6100		4	PLAIN-DB	72MM DIA.	5 X 7MM DIA.	95	R22	AITCHISON	1.70
C1107 (11 1/2")	6155* (3mm)		5	PLAIN-DB	50MM DIA.	7 X 7MM DIA.	101.6		SHEARER	2.80
12" (318mm) Coulters										
6242			3	PLAIN-DB	49.2MM DIA.	6 X 6.3MM DIA.	73	R44	BETTISON	
C1208	6281		3	PLAIN-DB	52.5MM DIA.	8 X 10.3MM DIA.(2 sets)	95.2	R23	Duncan	1.80
C1208W	6281R		3	FLUTED	52.5MM DIA.	8 X 10.3MM DIA.(2 sets)	95.2	R23	Duncan - 25 Flute	1.80
C1208D2*			3	DIRECTA 20 W	52.5MM DIA.	8 X 10.3MM DIA.(2 sets)	95.2	R23	Duncan 20 Wave	1.80
C1208D3*			3	DIRECTA 30 W	52.5MM DIA.	8 X 10.3MM DIA.(2 sets)	95.2	R23	Duncan 30 Wave	1.80
C1208T			3	THUNDER 25W	52.5MM DIA.	8 X 10.3MM DIA.(2 sets)	95.2	R23	Duncan 25 Wave	1.80
C1211			4	PLAIN-DB	55MM DIA.	5 X 12.7MM	95		Agroplow	1.80
13" (340mm) Coulters										
C1320	6336		3	PLAIN-DB	72MM DIA.	5 X 9MM DIA.	95	R22	CSN470 & 8000 DRILLS	2.00
6337			5	PLAIN-DB	50MM DIA.	5 X 7MM DIA.	101	R40	SHEARER	3.75
14" (356mm) Coulters										
C1405	6350		3	PLAIN-SB	50MM DIA.	6 X 7MM DIA.	73	R44	BT,WA	2.40
C1411			4	PLAIN-DB	55MM DIA.	5 X 12.7MM	95		Agroplow	2.40
C1435	6357		4	PLAIN-DB	63MM DIA.	5 X 13MM DIA.	108	R14	HOLDEN HT Hub,	2.80
C1435D2			4	DIRECTA 20 W	63MM DIA.	5 X 13MM DIA.	108	R14	HOLDEN HT Hub,	2.80
15" (381mm) Coulters										
6380			3	PLAIN-SB	30MM DIA.	6 X 8.3MM DIA.	74.4	R24	CJD & KINZE PLANTERS	3.50
C1504			4	PLAIN-SB	38.5MM DIA.	6 X 8.3MM DIA.	76.2		Morris Express, PHM	3.60
C1504S			4	SCALLOP	38.5MM DIA.	6 X 8.3MM DIA.	76.2		PHM	3.60
C1505			4	PLAIN-SB	60MM DIA.	6 X 10MM DIA.	90		Sow Ezy	3.60
C1505S			4	SCALLOP	60MM DIA.	6 X 10MM DIA.	90		Sow Ezy	3.60
C1506			4	PLAIN-SB	NCH	6 X 8MM DIA.	70.5		Horsch Serto	3.60
16" (406mm) Coulters										
6425	ALSO 6424		3	PLAIN-SB	25MM DIA.	6 X 7MM DIA.	73	R26	MASON PLANTER, EXEL	3.20
6406			4	PLAIN-DB	32MM SQ.	BLANK			BLANK: CUTTING CHARGES APPLY	4.15
C1600			4	PLAIN-DB	20MM DIA.	BLANK			BLANK	4.15



Agpoint Australia

Agpoint Boron Discs & Coulters.....Your Guarantee of Quality!!!
Recommended Retail Price List No. 179 Effective 1st November 2023 (GST Not Included)



Please Note: Prices Subject To Change Without Prior Notice

Part No	Similar To McCOY	R.R.P	Gauge mm	Style	Centre Hole	Radial Holes	P.C.D. mm	Radial Code	Application	Unit KG
16" (406mm) Coulters Cont										
C1635	6407		4	PLAIN-DB	63MM DIA.	5 X 13MM DIA.	108	R14	HOLDEN HT Hub	4.15
C1635W			4	FLUTED	63MM DIA.	5 X 13MM DIA.	108	R14	HOLDEN HT hub - 50 Flute	4.15
C1635D2			4	DIRECTA 20 W	63MM DIA.	5 X 13MM DIA.	108	R15	HOLDEN HT hub 20 Wave	4.15
C1650 OR 6422	Priced to Quit		4	PLAIN-SB	45MM DIA.	4 X 10.5MM CSK 80° DIA.	76	R72	Janke post 2007 (GWT 6422)	4.15
6424			4	PLAIN-SB	25MM DIA.	6 X 7MM DIA.	73	R26	MASON PLANTER, EXEL	4.15
6426			4	PLAIN-SB	45MM DIA.	4 X 10.5MM	76	R25	EXCEL PLANTER	4.15
6430			4	PLAIN-SB	75MM DIA.	13MM SQ.	108	R27	EXCEL STUBBLE WARRIOR	4.15
6432			4	PLAIN-SB	25MM DIA.	BLANK			BLANK: CUTTING CHARGES APPLY	4.15
6433			4	PLAIN-SB	75MM DIA.	13.5MM DIA.	108	R70	EXCEL STUBBLE WARRIOR	4.15
6434			4	PLAIN-SB	75MM DIA.	5 X 13.5MM CSK 80° DIA	108	R75	EXCEL STUBBLE WARRIOR	4.15
C1697			5	PLAIN-SB	48MM DIA.	6 X 9MM CSK 90° DIA	111		K-Hart Yetter (WA stocks only)	4.85
C1698			4	PLAIN-SB	69MM DIA.	5 X 13.5MM CSK 80° DIA	108		BOSS	3.70
18" (458mm) Coulters										
C1800			4	PLAIN-DB	20MM DIA.	BLANK			BLANK: CUTTING CHARGES APPLY	5.50
C1800T			4	THUNDER 25W	20MM DIA.	BLANK			25 Wave BLANK	5.50
C1800D2			4	DIRECTA 20 W	20MM DIA.	BLANK		R28	20 Wave BLANK	5.50
C1810WV	6438		4	8 WAVE	88mm DIA.	4 X 14MM DIA.	133	R30	Gyral	5.50
C1840RF			4	PLAIN-DB	80MM DIA.	5 X 14.3MM DIA.	108		WILLIAMS SEEDER	
C1840RFS			4	SCALLOPED	80MM DIA.	5 X 14.3MM DIA.	108	R14		
6441*			4	24 WAVE	64MM DIA.	5 X 13MM DIA.	108	R14	Suits Holden Hub	5.50
C1860	6457		4	PLAIN-DB	63MM DIA.	5 X 13MM DIA.	108	R14	Suits Holden Hub	5.50
C1860W	6473		4	FLUTED-DB	63MM DIA.	5 X 13MM DIA.	108	R14	Suits Holden Hub - 50 Flute	5.50
C1860WV	6440		4	12 WAVY-DB	63MM DIA.	5 X 13MM DIA.	108	R14	Suits Holden Hub - 12 Wave	5.50
C1860D2			4	DIRECTA 20 W	63MM DIA.	5 X 13MM DIA.	108	R14	Suits Holden Hub 20 Wave	5.50
C1860T			4	THUNDER 25W	63MM DIA.	5 X 13MM DIA.	108		Suits Holden Hub 25 Wave	5.50
C1860S			4	SCALLOPED	63MM DIA.	5 X 13MM DIA.	108		Suits Holden Hub	5.50
C1870	6480		5	PLAIN-SB	77MM DIA.	4 X 10.5MM DIA	112	R29	JD-FE G'minator, JD1890 <small>replace JD N283804/N214190</small>	5.90
C1871	6482		6	PLAIN-SB	77MM DIA.	4 X 10.5MM DIA	112	R29	Excel , JD-FE G'minator, JD1890	5.90
C1872	6472		6	PLAIN-SB	63MM DIA.	5 X 13MM DIA.	108	R14	Suits Holden Hub	7.00
C1873			4	PLAIN-DB	77MM DIA.	5 X 13MM DIA.	108		Suits Holden Hub, Gason	5.50
C1880W			4	FLUTED-DB	100MM DIA.	4 X 13.5MM DIA.	133.4		GREAT PLAINS (WA stocks only)	5.50
C1880WV			4	12 WAVY-DB	100MM DIA.	4 X 13.5MM DIA.	133.4		GREAT PLAINS - 12 Wave	5.50
C1880D2			4	DIRECTA 20W	100MM DIA.	4 X 13.5MM DIA.	133.4		GREAT PLAINS 20 Wave	5.50
C1880T			4	THUNDER 25W	100MM DIA.	4 X 13.5MM DIA.	133.4		GREAT PLAINS 25 Wave	5.50



Agpoint Australia

Agpoint Boron Discs & Coulters.....Your Guarantee of Quality!!!
Recommended Retail Price List No. 179 Effective 1st November 2023 (GST Not Included)



Please Note: Prices Subject To Change Without Prior Notice

Part No	Similar To McCOY	R.R.P	Gauge mm	Style	Centre Hole	Radial Holes	P.C.D. mm	Radial Code	Application	Unit KG
18" (458mm) Coulters Cont.										
C1890WV			4	13 WAVY-DB	68MM DIA.	4 X 12.5MM DIA.	100		WALKER (WA stocks only)	5.50
C1891			4	PLAIN-SB	68MM DIA.	4 X 12.5MM DIA. CSK	100		WALKER (WA stocks only)	5.50
6483	6483		4	PLAIN-SB	25MM DIA.	BLANK			BLANK: CUTTING CHARGES APPLY	5.50
C1892			5	PLAIN-SB	68MM DIA.	4 X 12.5MM DIA. CSK	100		WALKER (WA stocks only)	5.90
C1893			5	PLAIN-SB	94MM DIA.	4 X 13.5MM DIA.	127		AMITY	5.90
C1897			6	PLAIN-SB	93MM DIA.	4 X 15.8MM DIA. CSK	127		BOSS, BARTON OPENER (FLEXICOIL), PILLAR	5.90
C1898	6481		5	PLAIN-SB	93MM DIA.	4 X 15.8MM DIA. CSK	127	R61	NEW BOSS, BARTON DISC OPENER (FLEXICOIL), PILLAR	5.90
20" (508mm) Coulters										
C2000			6	PLAIN-DB	20MM DIA. PILOT HOLE	BLANK			BLANK	9.20
C2000T			5	THUNDER 25W	20MM DIA. PILOT HOLE	BLANK			Blank 25 Wave	7.50
C2015	6507		4	PLAIN-DB	63MM DIA.	5 X 13MM DIA.	108	R14	Suits Holden Hub,Y,SF,SR	7.50
C2025			6	PLAIN-DB	96MM DIA.	6 X 13MM DIA.	122		Suits Horsch, Avitar	
C2060			5	PLAIN-DB	63MM DIA.	5 X 13MM DIA.	108		Suits Holden Hub	8.50
C2060D2			5	DIRECTA 20 W	63MM DIA.	5 X 13MM DIA.	108	R14	Suits Holden Hub 20 Wave	7.50
C2060T			4	THUNDER 25W	63MM DIA.	5 X 13MM DIA.	108		Suits Holden Hub 25 Wave	7.50
C2067W			5	FLUTED-DB	63MM DIA.	4 X 12MM DIA.	132		Suits HORSCH SPRINTER - 60 Flutes	8.50
C2070	6522		6	PLAIN-DB	63MM DIA.	5 X 13MM DIA.	108	R14	Suits HT Hub,Y,GS,CS GIANT	9.50
6524			6	PLAIN-DB	25MM DIA.	BLANK			BLANK: CUTTING CHARGES APPLY	9.50
6510			6	PLAIN-SB	25MM DIA.	BLANK			BLANK: CUTTING CHARGES APPLY	9.50
6530			6	PLAIN-DB	81MM DIA.	5 X 13MM DIA.	108		Suits Holden Hub, EXCEL	9.50
C2072	6523		6	PLAIN-SB	63MM DIA.	5 X 13MM DIA.	108	R14	Suits HT Hub,Y,GS,JK,Y	9.50
C2083D2			5	DIRECTA 20 W	83MM DIA.	5 X 13MM DIA.	108		Mooses, East, PMD, HT Hub - 20 Waves	8.50
C2090W			5	FLUTED-DB	68MM DIA.	4 X 12.5MM DIA. CSK	100		PRIMARY SALES, WALKER	8.50
C2091			6	PLAIN-SB	68MM DIA.	4 X 12.5MM DIA. CSK	100		WALKER (WA stocks only)	9.50
22" (558mm) Coulters										
C2272			6	PLAIN-SB	63MM DIA.	5 X 13MM DIA.	108		Suits HT Hub,Y,GS,JK,Y, Austill	10.50
24" (610mm) Coulters										
6624	USE 6MM BLANK		5	PLAIN-DB	102M DIA.	5 X 16MM DIA.	140	R59	NOBLE BLADE PLOUGH	12.30
6601			6	PLAIN-DB	25MM DIA.	BLANK			BLANK: CUTTING CHARGES APPLY	14.70
C2440			8	PLAIN-SB	95MM DIA.	4 X 13MM DIA.	127		Milne-Daybreak	16.36
C2472	6627		6	PLAIN-SB	63MM DIA.	5 X 13MM DIA.	108	R14	Tobin Speed Drill, Holden HT Hub	14.70



Agpoint Australia

Agpoint Boron Discs & Coulters.....Your Guarantee of Quality!!!
Recommended Retail Price List No. 179 Effective 1st November 2023 (GST Not Included)



Please Note: Prices Subject To Change Without Prior Notice

Part No	Similar To McCOY	R.R.P	Gauge mm	Style	Centre Hole	Radial Holes	P.C.D. mm	Radial Code	Application	Unit KG
26" (650mm) Coulters										
C2600	6669		6	PLAIN-DB	25MM DIA.	BLANK			BLANK: CUTTING CHARGES APPLY HGE HGE BONEL HOLDEN HT HUB,GS,Y EXCEL EXCEL	18.00
C2608	6667		6	PLAIN-DB	46MM DIA.	4 X 18MM DIA.	165.2			18.00
C2609			6	PLAIN-DB	51MM DIA.	4 X 14.3MM SQ CSK.	165.2	R31		18.00
C2610	6670		6	PLAIN-DB	102MM DIA.	8 X 12.3MM DIA	292			18.00
C2612			6	PLAIN-DB	64MM DIA.	5 X 13MM DIA.	108			18.00
6673*			6	PLAIN-SB	108MM DIA.	6 X 14MM DIA.	140	R34		18.00
6672			8	PLAIN-SB	108MM DIA.	6 X 14MM DIA.	140	R34		18.00
28" (700mm) Coulters										
C2808			6	PLAIN-DB	46MM DIA.	4 X 18MM DIA.	165.2			20.70
30" (762mm) Coulters										
C3014			6	PLAIN-DB	102MM DIA.	8 X 12MM DIA.	292		BNL,McLEOD,P&H,HGE	24.00
C3015			6	PLAIN-DB	51MM DIA	4 X 18MM DIA.	165.2			24.00
6767			9	PLAIN-DB	30MM DIA	BLANK	165.2		BLANK: CUTTING CHARGES APPLY BNL,HGE,MSW EXCEL	37.00
C3040	6776		9	PLAIN-DB	51MM DIA	4 X 18MM DIA./8 x 12.3 Dia.	165.2/292	R31		37.00
6777			9	PLAIN-DB	108MM DIA	6 X 14MM DIA.	140	R34		37.00

8 Wave: 38mm-40mm

Suitable for sandy soils because of its large waves and great tilled strip width. It needs quite an effort for soil penetration

12 Wave: 18mm-20mm

Suitable for sandy &/or very damp, sticking soils. It needs less vertical effort to penetrate into the ground than the 8 wave coulters.

25 Wave/Flute: 14mm-16mm

Suitable for clayish soils and regularly used for minimum till practices. The Directa coulters is quite often a preferred option. It needs less effort for soil penetration. Good performance for cutting straw.

20 Wave Directa: 10mm-12mm

The tangential wave design allows the blade flute to attack the residue vertically providing improved cutting, penetration and decreased hair pinning. It has the advantage of reducing soil stirring to the minimum due to the narrower tilled strip it leaves.

50 Wave/Flute or 30 Wave Directa: 8mm-10mm

Used for planting grass and for no till on clayish soils. Slight vertical force required to penetrate but the bigger the diameter the greater the force needed. Smooth edge coulters show a superb rotating performance due to wave-soil contact. Wavy/Fluted edge coulters perform better at straw cutting.